

ARTICLE DATA SHEET



Article no.: 3292

Product range: VEROFLEX

Material type: 100 % Polyester (PES), Jacquard-Crush, pearlescent coating FR

Weight: 103 gr/m²

Thickness: 0,26mm

Widths: 2300mm (roller & plissee)

Maintenance instr.: can be cleaned with a slightly humid towel (not washable)

Specifications:

- outer side: pearlescent coating FR
- Flame-retardant properties tested and certified:
 - B1 acc. DIN 4102
- Ecologically friendly acc. to OEKO-Tex Standard 100
 - no PVC
 - may contain traces of halogen due to the FR-coating
- Lightfastness acc. to DIN EN ISO 105 B02: 5 - 6
- not suitable for humid areas

COLOR	Visual optical figures			Solar optical figures			UV-Transm.	F _c -value*	Total energy transm.*
	exterior			exterior				DIN EN 14501 * g-glass 0.70	DIN EN 13363-1 * g-glass 0.70
	Rv	Tv	Av	Rs	Ts	As	t _{UV}	F _c	g _{tot}
1	66%	29%	5%	59%	34%	7%	6%	0,58	41%
3	57%	14%	29%	56%	27%	17%	2%	0,60	42%
4	63%	23%	14%	58%	30%	12%	3%	0,59	41%
5	67%	27%	6%	59%	31%	10%	3%	0,58	41%
7	55%	12%	33%	54%	26%	20%	2%	0,61	43%
9	64%	24%	12%	59%	30%	11%	3%	0,58	41%

